





PRODUCT DETAILS

NATURE'S HOME.

Superior Indoor Air Quality Solutions

The 36H32-214 is a New Universal Replacement Gas Valve from White-Rodgers - for contractors that replace gas valves in residential and commercial gas-fired forced-air furnaces. 36H Series valves perform reliably in the field in many different applications.

 $\frac{1}{2}$ " x $\frac{1}{2}$ " Gas Valve

The unique 36H32-214 gas valve competes well against the competition. Installation is fast and easy with the $\frac{1}{2}$ x ½ inch NPT ports. It matches well with OEM gas valve types without the need to use reducer bushings - saving time on installations.

FEATURES

- HSI / DSI / Intermittent / Proven Pilot
- 24VAC, 60 Hz
- 1/2 x 1/2 NPT, straight thru
- Inlet / outlet pressure taps and screens
- Regulator setting: 3.5 in WC at 100,000 BTU/HR
- Range of Regulation 40,000 to 240,000 BTU/Hr
- (3) 1/4 in male spade terminals
- Electric On/Off switch
- LP conversion kit included UPC 786710550089

Voltage	Type of Gas	Pipe Size		- I	Stages	HSI/DSI	Proven Pilot	Standing Pilot
24 Volt	Nat./LP	1/2 X 1	/2 Fast		1	Yes	Yes	No
	Intermit		Convertible Nat/LP	Bus	ducer shing	Inlet & Outlet	Side	

Pilot Yes	Kit Included Yes	Kit No	Pressure Tap Yes*	Taps No		
165	165	INO	Tes	NO		
	1" PD Capaci	ty	Rated Range of Regulati			

	1″ PD C	apacity	Rated Range of Regulation		
	BTU/HR		BTU/HR		
	Std. Gas .64	LP Gas 1.53	Std. Gas 1.53	LP Gas .64	
Pipe Size	Sp. Gr. (1000	Sp. Gr. (2500	Sp. Gr. (2500	Sp. Gr. (1000	
(36 H)	BTU/CU FT)	BTU/CU FT)	BTU/CU FT)	BTU/CU FT)	
1/2" x 1/2"	170,000	275,500	40,000 to	40,000 to	
	100		240,000	400,000	

